

Compression Sprayer

for lubricants

Article no.: 9930

Description

- 🌿 The perfect helper for professional applications and It offers plenty of comfort
- 🌿 such as an ergonomic shut-off valve with integrated filter and an integrated compressed air-filler valve.
- 🌿 Stainless steel tank, FPM/FKM seals.
- 🌿 Equipment with carrying frame possible.

Application area



Performance Features

- 🌿 Nozzle for liquids requiring fine distribution
- 🌿 Incl. compressed air-filler valve with plug-in coupling (size 7.2) and pressure relief valve for connection to a compressor
- 🌿 The funnel cover prevents dirt contaminating the spraying agent and protects against contamination and clogging of the nozzle.
- 🌿 Stocked spare parts compartment with spare seals
- 🌿 Pump holder prevents soiling of the pump when filling.
- 🌿 Spray and extension wand bracket for space-saving and safe storage
- 🌿 Base with foot ring for a sturdy foothold when pumping
- 🌿 Extra-large filling opening with integrated filling funnel for simple filling and emptying without any spillage.
- 🌿 Safety latch on the shut-off valve prevents unintentional spraying.
- 🌿 Ergonomic shut-off valve with filter helps protect your wrist. Filter is easy to clean and prevents clogging of the nozzle.
- 🌿 Can be equipped with round, flat or full cone nozzle.
- 🌿 Spiral hose PU 2m, blue with plug-in coupling.

Usable for

Lubricants NLGI 00/000 and fluids.

- 🌿 SwitchLub 60/35
- 🌿 SwitchLub 60/09
- 🌿 SyntLub 4000

Technical data

Filling content:	6.0 l (1.59 gal)
Total content	9.0 l (2.38 gal)
Max. operating pressure:	6 bar (88 psi)
Tare weight:	approx. 4.30 kg Carrying frame: 1.95 kg
Tank:	Stainless steel
Seals:	FPM/FKM
Scope of application:	pH 5 - 9*
Nozzle:	65° full jet, 80 - 01 E, 1.1 mm, with filter, Brass, Flat jet nozzle
Spray wand:	360° rotatable, 50 cm, Brass, curved
Hose:	250 cm, with safety interlock, Spiral hose
Safety valve:	replaceable
Manometer:	Pressure gauge with indicator
Pump:	Brass with steel piston rod and 2-handed handle



Compression Sprayer



with carrying rack